




Parts Manual



W8L

**Power Controlled &
Electronic Controlled
Towing Winch
for Caterpillar Dozers**

A Product of

Allied Systems
COMPANY

Sherwood, OR USA

Please check the Allied Systems website
regularly for updates to this manual.
www.alliedsystems.com

Safety Precautions


**Read, understand and observe the Safety Summary
on pages 0-3 through 0-5
to prevent injury to personnel and damage to equipment.**

Winch serial number _____

Date put into service _____

**NOTE: This publication may be translated to different languages for sole purpose
of easy reference in non-English speaking locations.
Should there be differences in interpretations to the text,
please refer to the English language edition published by Allied Systems Company
as the controlling document.**

Index - Illustrated



Ref	Item	Page
1	Frame/Covers/Decals/Parts-Mounting	1
2	Gear Train/Shaft	13
3	Hydraulics/Controls	35
4	Optional Equipment	55
5	Recommended Service Kits	59
6	Numerical Index	75

Index - Master

<u>Description</u>	<u>Page No.</u>
Brake.....	27
Brake Assembly Kit - 2311155	68
Brake Shaft.....	25 thru 26
Brake Shaft Bearing Kit, Gear Ratio 9 - 2311159.....	70
Brake Shaft Bearing Kit, Gear Ratios 1, 3 - 2311158.....	69
Clutch	22 thru 24
Clutch Shaft Bearing Kit, Gear Ratio 9 - 2311163	72
Clutch Shaft Bearing Kit, Gear Ratios 1, 3 - 2311162	71
Clutch Shaft Kit, Gear Ratio 9 - 2311157	67
Clutch Shaft Kit, Gear Ratios 1, 3 - 2311156	66
Clutch/Bevel Gear Shaft	18 thru 21
Control Valve Assembly	45
Drum & Intermediate Shaft Bearing and Seal Kit - 2311164	73
Drum Shaft Group.....	30 thru 33
Fairlead.....	56 thru 57
Filter Kit, E-Controls - 2311168.....	63
Filter Kit, P-Controls - 2311167.....	62
Frame/Covers	2 thru 3
Gasket Kit - 277341W.....	64 thru 65
Gear Box Assembly	14 thru 15
Handlever	53
Handlever Assembly.....	52
Handlever Installation, Power Controls	49 thru 51
Hydraulic Group, E-Controls	40 thru 44
Hydraulic Group, P-Controls	36 thru 39
Intermediate Gear Shaft	28
Joystick Installation, E Controls	54
Miscellaneous Parts	74
Mounting Parts	4 thru 9
Nameplate & Decals.....	10 thru 11
PTO Shaft	16 thru 17
Pump.....	47 thru 48
Recommended Service Kits	61
Recommended Winch Service Intervals.....	60
Specialized Tools.....	74
Valve Manifold Assembly	46
Wire Rope Assemblies	74
Wire Rope Assemblies	58

Safety Summary

General Safety Notices

The following pages contain general safety warnings which supplement specific warnings and cautions appearing elsewhere in this manual. All electrical and hydraulic equipment is dangerous. You must thoroughly review and understand the Safety Summary before attempting to operate, troubleshoot or service this winch.

The following symbols and terms are used to emphasize safety precautions and notices in this manual:



DANGER

The “DANGER” symbol indicates a hazardous situation which, if not avoided, will result in serious injury or death. Carefully read the message that follows to prevent serious injury or death.



WARNING

The “WARNING” symbol appears wherever incorrect operating procedures or practices could cause serious injury or death. Carefully read the message that follows to prevent serious injury or death.



CAUTION

The “CAUTION” symbol appears where a hazardous situation which, if not avoided, could result in minor to moderate injury and equipment damage.

NOTICE

This signal word alerts to a situation that is not related to personal injury but may cause equipment damage.

NOTE: ...

The term “NOTE” highlights operating procedures or practices that may improve equipment reliability and/or personnel performance.

NOTE: All possible safety hazards cannot be foreseen so as to be included in this manual. Therefore, you must always be alert to potential hazards that could endanger personnel and/or damage the equipment.

Safety Regulations

Each country has its own safety legislation. It is in the operator's own interest to be conversant with these regulations and to comply with them in full. This also applies to local bylaws and regulations in force on a particular work site.

Should the recommendations in this manual deviate from those in the user's country, the national regulations should be followed.

Operation, Inspection, and Maintenance Warnings




WARNING

Obey the following cautions and warnings before using your winch to avoid equipment damage, personal injury or death.

- Do not operate the winch unless you are authorized and trained to do so.
- Do not operate the winch unless the vehicle is equipped with a screen to protect the operator if the wire rope breaks.
- Read, understand, and follow the operating, inspection, and maintenance instructions in this manual.
- Do not use the control levers for hand holds when entering or leaving the vehicle.
- Do not permit other people near the control area when you inspect or repair a machine.
- Never inspect, repair, or perform maintenance on a machine that is in motion.
- Inspect the winch before each use:
 - » Make sure that the controls and instruments operate correctly.
 - » Report the need for repairs immediately.
 - » Do not work with a damaged or worn wire rope.
 - » Do not use a winch that needs repairs.

- » If the wire rope and ferrule must be removed from the drum, make sure the end of the wire rope and ferrule are controlled when the ferrule is released. The end of the wire rope can suddenly move from the drum like a compressed spring when the ferrule is released, and cause an injury.
- Stay in the operator's seat when operating the winch.
- Do not stand on the vehicle when operating the winch.
- Avoid winch operation near people or other machines.
- Never stand nor permit others to stand in the bight (loop) of a wire rope.
- Do not stand nor permit others to be near the winch or wire rope when there is tension on the wire rope.
- Observe job site rules.
- Be in complete control at all times.
- Do not use the control levers as hangers for clothes, water bags, grease guns, lunch pails, etc.
- Do not leave the vehicle when the winch wire rope is under tension.
- Do not permit riders on the vehicle or load.
- Do not use the winch as an anchor for a double or two-part line.
- Do not pull the hook through the throat or over the drum, which will cause damage.
- When the winch is not in use, make sure the control lever is in **BRAKE-ON** position and the winch brake is applied.
- Do not use winch as a hoist. Tractor and skidder mounted winches are designed for towing.
- Always inspect wire rope, tail chain and other rigging components for wear, damage, broken strands or abuse before use.
- Never use wire rope, tail chain or other rigging that is worn-out, damaged or abused.
- Never overload wire rope, tail chain or rigging.
- Wire rope and tail chain will fail if worn-out, overloaded, misused, damaged, improperly maintained or abused. Wire rope or tail chain failure may cause serious injury or death!



- Do not terminate wire rope to tail chain by the use of a knot.
- Do not handle wire rope if the hook end is not free. A load could break away, suddenly tensioning the wire rope, resulting in serious injury or death.
- Stay clear of wire rope entry areas (fairlead or arch rollers, winch drum etc).
- Make sure ground personnel are in plain view of the operator, and at a distance of at least 1½ times the working length of the wire rope.
- Make sure that any hand signals used by ground personnel are clearly defined and understood by everyone involved.
- Do not attempt to "jerk" or "shock" a load free. Doing so can cause loads in excess of the rated capacity of the wire rope, winch, or mounting hardware.
- Replace any parts only with genuine Allied Winch parts.
- **Maintain a minimum of three (3) complete wraps of wire rope** on the drum for normal operation. It may help to paint the last five wraps of wire rope a contrasting color, to serve as a visual indicator.

- Do not handle wire rope with bare hands. Wear leather gloves at all times.
- Align the tractor with the load to prevent side loading the winch, and to maintain even spooling of the wire rope.
- If applying tension to the wire rope manually during spooling:
 - » ensure that the operator is winching in slowly,
 - » keep your hands and clothing well clear of any rollers or the winch drum,
 - » do not maintain tension by letting the wire rope to slip through your hands,
 - » use a hand-over-hand technique to maintain tension.
- Be aware of the ground conditions, and make sure the ground and tractor are stable enough to pull the intended load.
- Do not attempt to pull loads in excess of the rated capacity of the winch.
- Keep yourself informed of any applicable codes, regulations and standards for the job.
- Your winch may have temperature shut-off system for protection of tractor and winch. Manual override of high temperature shut-off will cause damage to tractor and winch.
- This winch is neither intended, designed, nor rated for any application involved in the lifting or moving of personnel.
- Use only the lubricants listed in the Recommended Oil List. See page 0-11.
- Do not weld on any part of the winch. Contact Allied Systems if weld repairs are needed.
- The hydraulic system must be kept clean and free of contamination at all times.
- Be aware of the hazards of pressurized hydraulics:
 - » Wear personal protective equipment, such as gloves and safety glasses, whenever servicing or checking a hydraulic system.
 - » Assume that all hydraulic hoses and components are pressurized. Relieve all hydraulic pressure before disconnecting any hydraulic line.
 - » Never try to stop or check for a hydraulic leak with any part of your body; use a piece of cardboard to check for hydraulic leaks.
 - » Small hydraulic hose leaks are extremely dangerous, and can inject hydraulic oil under the skin, even through gloves.
 - » Infection and gangrene are possible when hydraulic oil penetrates the skin. See a doctor immediately to prevent loss of limb or death.



Identification - Unit

Allied Winch S/N Nameplate Data For Tractor Mountings




Figure 1 - Tractor Identification

Tractor Make Model and Starting Tractor Serial Number Where Applicable	
C O D E	C Caterpillar
715	D6GC ③
72	D7R SERIES II ①③⑨
721	D7 BUILD 17A ⑨

Capacities and Specifications

Recommended Oil List

Recommended Oils* - General Conditions			
Manufacturer	Oil Type	Ambient Temperature Range	
		°F	°C
ExxonMobil	Mobil Fluid 424 (Factory fill)	-13 to 104	-25 to 40
John Deere	Hy-Gard™	-13 to 122	-25 to 50
Chevron	1000 THF	-13 to 104	-25 to 40
Caterpillar	Multipurpose Tractor Oil (MTO)	-13 to 104	-25 to 40
Case	Hy-Tran Ultra	-20 to 122	-29 to 50

Recommended Oils* - Low Temperature Conditions			
Manufacturer	Oil Type	Ambient Temperature Range	
		°F	°C
ExxonMobil	Mobil Fluid LT	-40 to 86	-40 to 30
John Deere	Low Viscosity Hy-Gard	-40 to 86	-40 to 30
Chevron	THF W	-40 to 86	-40 to 30

* Note: Use of non-recommended oils may void warranty.

Figure 2 Recommended Oil List

Note: Refer to Winch Maintenance decal on page 23 for more information.

Winch Oil Capacity

Winch Model	Oil Capacity
W8L	20.0 Gallon (76 L)

Note: The gear box uses 0.5 gallon oil, and is separate from the winch.

Figure 3 Winch Oil Capacity

Intentionally Blank

Section 1


Frame/Covers/Decals/Mounting Parts

Frame/Covers	2 thru 3
Mounting Parts.....	4 thru 9
Nameplate & Decals	10 thru 11

Covers


AW8LP*****C***

(All Installations with Power Controls)



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
3	95959W	1	Pin, Drawbar	335	2305270W	1	Cover, Valve
4	2303221W	1	Pin, Retaining	336	2314805	2	Gasket
47	196279W	1	Rod, Tie	343	2303848W	26	Screw, Flange
48	15272W	2	Cotter Pin	352	2303902W	11	Screw, Flange
49	222262W	2	Plug	354	142761W	1	Gasket
50	14595W	1	Fitting	355	15319W	1	Fitting
152	286043W	1	Cover, Brake	356	21420W	1	Breather
153	286044W	1	Gasket	357	2300962W	1	Cap, Breather
165	2303848W	25	Screw, Flange	365	192956W	1	Cover, RH Side Frame
332	2314804	2	Gasket	450	253814W	1	Cover, Top
333	2304708W	1	Cover Plate				
334	2314005	2	Gasket, Filter Cover				


Covers
AW8LE***C*****
(All Installations with Electronic Controls)



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
3	95959W	1	Pin, Drawbar	405	2303848W	24	Screw, Flange
4	2303221W	1	Pin, Retaining	406	2303902W	11	Screw, Flange
47	196279W	1	Rod, Tie	407	142761W	1	Gasket
48	15272W	2	Cotter Pin	408	15319W	1	Fitting
49	222262W	2	Plug	409	21420W	1	Breather
50	14595W	1	Fitting	410	2300962W	1	Cap, Breather
152	286043W	1	Cover, Brake	411	Y25G-0416	2	Capscrew
153	286044W	1	Gasket	412	2317364	2	Stud - 0.5 Dia X 1.75
165	2303848W	25	Screw, Flange	413	221771W	2	Washer
365	192956W	1	Cover, RH Side Frame	414	221711W	2	Hex Nut
400	2314804	2	Gasket	450	253814W	1	Cover, Top
401 *a	2317447	1	Cover, Filter (Allied Branded)	*a Used on AW8LE**C721, AW8LE**C72			
401 *b	2317346	1	Cover, Filter (Unbranded)	*b Used on AW8LE**C721N			
402	2314005	2	Gasket, Filter Cover				
403	2305270W	1	Cover, Valve				
404	2314805	2	Gasket				

Mounting Parts

AW8LP**C715 (CAT D7GC with P-Controls)



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
1	296434W	14	Washer	14	67355W	1'	Lockwire
2	*b 225065W	12	Capscrew	15	383158W	1	Spacer
3	292660W	2	Nut	16	90937W	1	O-Ring
4 *a*b	2315880	2	Stud	17	2315868	1	Pad, Tap
5	15887W	1	O-Ring	18	2315879	1	Pad, Tap
6	2307554W	6	Plug	19	2317399	1	Guard - Bottom
7	2313655	1	Bracket - Mounting, RH	20	296422W	4	Washer
8	2313656	1	Bracket - Mounting, LH	21	293645W	4	Capscrew
9	Y17C-2088	6	Capscrew				
10	225851	14	Washer				
11	221724W	6	Hex Nut				
12	166396W	2	Capscrew				
13	388655W	1	Capscrew				

*a Apply Anaerobic Adhesive / Sealant T70 230064W to threads in tractor rear face


*b Apply threadlocker 318702W to threads

Intentionally Blank

Mounting Parts

AW8LE**C721 (CAT D7 Build 17A with E-Controls)

Page 1 of 2



Mounting Parts


AW8LE**C721 (CAT D7 Build 17A with E-Controls)

Page 2 of 2

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
1.1	2315875	12	Stud				
1.2	225851	12	Washer	2.8	15070W	2	Nut
1.3	292661W	12	Nut	2.9	383158W	1	Spacer
1.4	15887W	1	O-Ring	2.10	90937W	1	O-Ring
1.5 *a	381181W	1	Guard, Cable	2.11	388655W	1	Capscrew
1.6 *a	129563W	1	Cable Tie	2.12	67355W	1'	Lockwire (Per Ft)
2.1	2317189	1	Bracket - Mounting, Top	3.1	398817W	12	Screw, Flange
2.2	378237W	1	Bracket - Mounting, RH	3.3	2317193	1	Guard, Bottom
2.3	378238W	1	Bracket - Mounting, LH	3.4	2303661W	1	Plate, LH Guard
2.4	271744W	4	Capscrew	3.5	2303662W	1	Plate - Guard, RH
2.5	166396W	2	Capscrew	3.6	2303664W	4	Plate, Tapped
2.6	1310819W	2	Capscrew	3.7	2314818	2	Tap Pad
2.7	225851	10	Washer				

*a Not Illustrated

Mounting Parts
AW8L***C72 (CAT D7R Series II)
Page 1 of 2




Mounting Parts

AW8L***C72 (CAT D7R Series II)

Page 2 of 2

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
1.1 *a	2315875	12	Stud	2.8	1310819W	2	Capscrew
1.1 *b	2306421W	12	Stud	2.11	90937W	1	O-Ring
1.2	225851	12	Washer	2.12	383158W	1	Spacer
1.3 *a	292661W	12	Nut	2.13	388655W	1	Capscrew
1.3 *b	221725W	12	Nut	2.14	67355W	1'	Lockwire (Per Ft)
1.4	15887W	1	O-Ring	3.1	398817W	12	Screw, Flange
1.5	381181W	1	Guard, Cable	3.3	2303660W	1	Guard, Bottom
1.6	129563W	1	Cable Tie	3.4	2303661W	1	Plate, LH Guard
2.1	378235W	1	Bracket - Mounting, Top	3.5	2303662W	1	Plate - Guard, RH
2.2	378237W	1	Bracket - Mounting, RH	3.6	2303664W	4	Plate, Tapped
2.3	378238W	1	Bracket - Mounting, LH	3.7	2314818	2	Tap Pad
2.4	225851	10	Washer	*a Used on AW8LP**C72			
2.5	166396W	2	Capscrew	*b Used on AW8LE**C72			
2.6	271744W	4	Capscrew				
2.7	15070W	2	Nut				

Rotate clamp 180°
to position shown.




Rear Face of Dozer

Nameplate & Decals

Page 1 of 2

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
1	2300008W	1	Decal, RH	6	2314343	1	Tag, Check Dropbox Oil
2	1321665W	1	Decal, Warning	7	137852W	1	Cable Tie
3 *a	2311481	1	Decal, PTO Winch Maintenance	11	16602W	4	Screw
4	2311330	1	Decal, Load & Wire Rope Safety				

*a Reference Parts Marketing bulletin PMB0801



Nameplate & Decals

Page 2 of 2

Contact Allied Systems
Winch Department if the
Nameplate Is Broken.




Contact Allied Systems
Winch Department if the
CE Mark Label Is Needed.



6, 7

**CHECK
DROP BOX OIL
BEFORE
OPERATION!**



PTO Winch Maintenance

Recommended Winch Service Intervals

Hours or **	Months **	Filter ***	Winch Gear Oil	Brake & Clutch	Major Overhaul
First 250	1	Change			
Every 500	3	Change			
Every 1,000	6		Change		
Every 5,000				* Inspect	
Every 10,000					* Evaluate

Lube rollers and check oil level and filter light weekly.

- * Evaluate = Service based on average winch use;
 - if used more than once a day, perform overhaul.
 - if used less than once a day, remove covers and check to determine need.
- * Inspect = Disassemble and inspect for wear.
- ** Service winch using the tractor's hour meter or the length of time the winch is mounted to the tractor, whichever occurs first.
- *** Follow tractor schedule if using tractor filter.

IMPORTANT - For best Load Control

Use only the following oils:

Caterpillar -Multipurpose Tractor Oil (MTO)

John Deere -Hy-Gard

ExxonMobil -Mobil Fluid 424 (Factory Fill)

Chevron -1000 THF

Consult service/operating manual for low temperature oils and other details. Use of non-approved oil may void warranty.



WINCH

3

4



Intentionally Blank

Section 2

Gear Train/Shaft

Gear Box Assembly	14 thru 15
PTO Shaft	16 thru 17
Clutch/Bevel Gear Shaft.....	18 thru 21
Clutch.....	22 thru 24
Brake Shaft	25 thru 26
Brake.....	27
Intermediate Gear Shaft	28
Drum Shaft Group.....	30 thru 33


Gear Box Assembly

1:1 Ratio


Page 1 of 2

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	1308406W		Assembly, Gear Box				
2	383156W	1	. Gear, Top 36T	17	29758W	1	. Cone, Bearing
3	388640W	1	. Gear, Idler 37T	18	45733W	1	. Cup, Bearing
4	15305W	1	. Plug	19	15303W	1	. Fitting
5	41212W	1	. Bearing	20	383167W	1	. Carrier
6	43307W	2	. Bearing	21	123270W	1	. Seal
7	388646W	1	. Race, Inner	22	*a 110931W	AR	. Shim .005
8	58947W	1	. Ring, Snap	23	*a 110932W	AR	. Shim .007
9	16984W	1	. O-Ring	24	*a 110933W	AR	. Shim .020
10	388642W	1	. Pin	25	178402W	6	. Capscrew
11	194090W	2	. Capscrew, Sealing	27	35504W	1	. Fitting
12	15156W	2	. Washer	40	374807W	1	. Shaft, Input
13	374803W	1	. Cup, Bearing	41	374795W	1	. Gear, Input 36T
14	374804W	1	. Cone, Bearing	42	374805W	1	. Washer, Support
16	12963W	1	. Ring, Snap	43	383178W	1	. Gearbox

*a Requires 264159W Sealant

Gear Box Assembly1:1 Ratio
Page 2 of 2


PTO Shaft
Gear Ratios 1, 6



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
58	134078W	AR	Shim, 0.005"	72	35573W	1	Snap Ring
59	134079W	AR	Shim, 0.007"	73	381190W	1	Shaft, PTO
60	67355W	AR	Lockwire	74	96020W	1	Gear, Bevel
61	169671W	6	Capscrew	78	79389W	1	Seal, Oil
70	98362W	1	Carrier	79	12916W	1	Snap Ring
71	45310W	1	Bearing - Ball				

PTO Shaft

Gear Ratios 2, 3, 7, 8, 9, 10



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
58	134078W	AR	Shim, 0.005"	73	285277W	1	Shaft, PTO (GR 2, 7)
59	134079W	AR	Shim, 0.007"	73	313884W	1	Shaft, PTO (GR 3, 8, 9, 10)
60	67355W	AR	Lockwire	74	79389W	1	Seal, Oil
61	169671W	6	Capscrew	75	133898W	1	O-Ring
70	98362W	1	Carrier	76	96524W	1	Spacer
71	45310W	1	Bearing - Ball	77	12944W	1	Snap Ring
72	35573W	1	Snap Ring				

Clutch/Bevel Gear Shaft

Gear Ratios 1, 3

Page 1 of 2

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
100	*a 287942W	1	Gear, 2nd Reduction Spider	224	224791W	1	Carrier - Bearing
111	*b 2302623W	1	Gear, 2nd Reduction Spider	225	35575W	1	Snap Ring - Ext
180	*c 96021W	1	Bevel Gear	226	174561W	1	Lockwasher
181	*d 96028W	1	Bevel Gear	227	21014W	1	Locknut
182	*e 313883W	1	Bevel Gear	228	224023W	1	Retainer, Bearing
200	287939W	1	Gear, Clutch	229	15307W	2	Fitting
201	96431W	1	Carrier	230	178402W	5	Capscrew
202	314848W	1	Clutch Shaft Assembly	231	15158W	7	Lockwasher
203	2302938W	1	Gear, Pump	232	225264W	2	Capscrew
204	256608W	1	Forward Clutch Assy (See pg 34)	233	225259W	AR	Shim, 0.005"
205	230405W	1	Bearing Cone	234	225260W	AR	Shim, 0.007"
206	174559W	1	Washer	235	225261W	AR	Shim, 0.020"
207	55289W	1	O-Ring	236	230351W	2	Bearing Cup
208	251733W	1	Spacer	237	196376W	1	Spacer
209	2310715	1	Carrier - Bearing	238	225255W	AR	Shim, 0.005"
210	41216W	1	Bearing - Ball	240	225256W	AR	Shim, 0.007"
212	230407W	2	Bearing, Roller	241	225257W	AR	Shim, 0.020"
213	58938W	2	Snap Ring	242	225262W	1	Bearing Cone
220	108877W	2	O-Ring	243	256609W	1	Clutch Assembly (See page 35)
221	39674W	2	O-Ring	245	2303848W	5	Screw, Flange
222	224024W	1	Retainer, Bearing				
223	95581W	4	Ring				

*a Used on Gear Ratio 1, 2, 3

*b Used on Gear Ratio 7

*c Used on Gear Ratio 1


*d Used on Gear Ratio 2, 7

*e Used on Gear Ratio 3

Clutch/Bevel Gear Shaft

Gear Ratios 1, 3

Page 2 of 2



Clutch/Bevel Gear Shaft

Gear Ratio 9

Page 1 of 2

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
100	287942W	1	Gear, 2nd Reduction Spider	510	55289W	1	O-Ring
182	313883W	1	Bevel Gear	512	*a 214495W	1	Capscrew
220	108877W	2	O-Ring	513	223428	1	Washer
221	39674W	2	O-Ring	521	2303574W	1	Reverse Clutch Assy (See pg 36)
222	224024W	1	Retainer, Bearing	523	2303548W	1	Gear
223	95581W	4	Ring	524	2303612W	1	Plate, Retainer Bearing
224	224791W	1	Carrier - Bearing	525	221771W	2	Washer
225	35575W	1	Snap Ring - Ext	526	221711W	1	Hex Nut
226	174561W	1	Lockwasher	527	200454W	1	Capscrew
227	21014W	1	Locknut	528	*b 2303562W	1	Spacer, 1.430"
228	224023W	1	Retainer, Bearing	528	*b 2303563W	1	Spacer, 1.435"
229	15307W	2	Fitting	528	*b 2303564W	1	Spacer, 1.440"
230	178402W	5	Capscrew	528	*b 2303635W	1	Spacer, 1.445"
231	15158W	7	Lockwasher	528	*b 2303636W	1	Spacer, 1.450"
232	225264W	2	Capscrew	528	*b 2306041W	1	Spacer, 1.455"
233	225259W	AR	Shim, 0.005"	528	*b 2306029W	1	Spacer, 1.460"
234	225260W	AR	Shim, 0.007"	528	*b 2306030W	1	Spacer, 1.465"
235	225261W	AR	Shim, 0.020"	528	*b 2310544	1	Spacer, 1.470"
236	230351W	2	Bearing Cup	528	*b 2310545	1	Spacer, 1.475"
237	196376W	1	Spacer	531	2303565W	1	Spacer, 2.272"
238	225255W	AR	Shim, 0.005"	532	2303554W	4	Bearing Cup
240	225256W	AR	Shim, 0.007"	533	2303555W	4	Bearing Cone
241	225257W	AR	Shim, 0.020"	534	2303556W	1	Bearing Cone
242	225262W	1	Bearing Cone	535	44326W	1	Bearing - Ball
243	256609W	1	Clutch Assembly (See page 35)	539	2303650W	1	Bearing, Needle
245	2303848W	5	Screw, Flange	546	1314435W	2	Shim
501	2303542W	1	Gear, Pump	547	230407W	1	Bearing, Roller
502	2303547W	1	Shaft Assembly	548	58938W	1	Snap Ring
507	2303545W	1	Shaft, Idler	590	2305276W	1	Gear, Clutch, 38T/19T
508	2303651W	4	Washer, Thrust				
509	2303543W	1	Gear, Pump				


*a Apply Threadlocker (318702W)

*b Select whichever spacer will obtain .003L to .002T bearing setting

Clutch/Bevel Gear Shaft


Gear Ratio 9

Page 2 of 2



Forward Clutch Assembly

Gear Ratios #1 (49.8:1), #3 (94.1:1)




Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	256608W		Assembly, Forward Clutch				
1	224790W	1	. Plate, Retainer	11	96468W	6	. Capscrew
2	*a 79972W	1	. O-Ring	12	141348W	1	. Plug
3	96462W	1	. Piston	13	196435W	6	. Set Screw
4	*a 261542W	8	. Plate, Separator	14	*a 39370W	1	. O-Ring
5	*a 328715W	8	. Disc, Friction	15	267505W	1	. Hub, Forward Clutch
6	*a 89777W	1	. O-Ring		19901W	1	. Pin, Slotted
7	*a 267499W	8	. Spring				
8	96461W	1	. Retainer, Spring				
9	*a 224793W	A/R	. Shim .031				
10	224794W	1	. Plate, Clutch				

*a Included in Service Kit 2310570.
 Qty 2 of 2310570 Included in Service Kit 2311156
 Qty 1 of 2310570 Included in Service Kit 2311157

Clutch Assembly

Gear Ratios #1 (49.8:1), #3 (94.1:1), #9 (94/102:1)




Note: This is the forward clutch assembly for winches with gear ratio #9, and is the reverse clutch for winches with gear ratios 1 and 3.

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	256609W		Assembly, Clutch				
1	224790W	1	. Plate, Retainer	11	96468W	6	. Capscrew
2 *a	79972W	1	. O-Ring	12	141348W	3	. Plug
3	96462W	1	. Piston	13	196435W	6	. Set Screw
4 *a	261542W	8	. Plate, Separator	14 *a	39370W	1	. O-Ring
5 *a	328715W	8	. Disc, Friction	15	257791W	1	. Hub, Reverse Clutch
6 *a	89777W	1	. O-Ring				
7 *a	267499W	8	. Spring	*a	Included in Service Kit 2310570.		
8	96461W	1	. Retainer, Spring	Qty 2 of 2310570 Included in Service Kit 2311156			
9 *a	224793W	A/R	. Shim .031	Qty 1 of 2310570 Included in Service Kit 2311157			
10	224794W	1	. Plate, Clutch				

Reverse Clutch Assembly

Gear Ratio #9 (94/102:1)




Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
Assembly, Reverse Clutch							
1	224790W	1	. Plate, Retainer	9	*a 224793W		. Shim .031
2	*a 89777W	1	. O-Ring	10	224794W	1	. Plate, Clutch
3	*a 79972W	1	. O-Ring	11	16373W	6	. Capscrew
4	96462W	1	. Piston, Clutch	12	141348W	1	. Fitting, Pipe
5	*a 261542W	6	. Plate, Separator	13	196435W	6	. Screw, Set - Special
6	*a 328715W	6	. Disc, Friction	14	*a 39370W	1	. O-Ring
7	*a 265407W	8	. Spring	15	2303573W	1	. Hub, Clutch
8	96461W	1	. Retainer, Spring				

*a Included in Service Kit 2300544W
Qty 1 of 2300544W Included in Service Kit 2311157

Brake Shaft

Gear Ratios #1, 2, 3, 7




Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
101 *a	95969W	1	Gear, 22T	167	203549	1	O-Ring
110 *b	2302622W	1	Gear, 44T	168	96417W	1	Gear, 19T
159	230311W	1	Bearing Cup	169	30080W	1	Bearing Cone
160	230310W	1	Bearing Cone	170	30059W	1	Bearing Cup
161	96433W	1	Retainer	380	12915W	2	Snap Ring
162	134081W	AR	Shim, 0.005"	381	133918W	1	Brake Shaft
163	134082W	AR	Shim, 0.007"				
164	134083W	AR	Shim, 0.020"				
165	2303848W	6	Screw, Flange				

*a Used with Gear Ratios #1, 2, 3

*b Used with Gear Ratio #7


Brake Shaft

Gear Ratios #8, 9, 10



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
101	95969W	1	Gear, 22T				
159	230311W	1	Bearing Cup	*c	2303637W	1	Spacer 2.168"
160	230310W	1	Bearing Cone	*c	2303638W	1	Spacer 2.173"
161	96433W	1	Retainer	*c	2310546	1	Spacer 2.178"
162	134081W	AR	Shim, 0.005"	*c	2310547	1	Spacer 2.183"
163	134082W	AR	Shim, 0.007"	*c	2310605	1	Spacer 2.188"
164	134083W	AR	Shim, 0.020"	*c	2310606	1	Spacer 2.193"
165	2303848W	6	Screw, Flange	559	2303571W	1	Bearing Cup
167	203549	1	O-Ring	560	2303572W	1	Bearing Cone
168	96417W	1	Gear, 19T	561	2303553W	1	Spacer, Long, Brake Shaft
169	30080W	1	Bearing Cone	563	12940W	1	Snap Ring
170	30059W	1	Bearing Cup	566	2303551W	1	Shaft - Brake
552	2303552W	1	Spacer, Short	581 *a	2303549W	1	Gear, 51T/29T
553	2303557W	1	Bearing Cup	591 *b	2305277W	1	Gear, 51T/35T
554	2303558W	1	Bearing Cone				
555	*c 2303567W	AR	Spacer 2.153"	*a	Used with Gear Ratio #8		
	*c 2303568W	AR	Spacer 2.158"	*b	Used with Gear Ratios #9, 10		
	*c 2303569W	AR	Spacer 2.163"	*c	Select whichever spacer will obtain .003L to .002T bearing setting		


Brake Assembly



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
4	196025W	1	Housing, Piston	16	328715W	10	Disc, Friction
5	140184W	8	Stud	17	261542W	9	Plate, Separator
7	133926W	1	Piston	21	265401W	1	Ring
8	133927W	1	Ring	22	193912W	1	Spring
9	79979W	1	O-Ring	23	196026W	1	Cover Plate
10	92867W	2	Pin	24	199594W	8	Hex Nut
11	252114W	1	Plate, Pressure	25	234271	8	Washer
12	12940W	2	Snap Ring	30	*a 2310475	1	Stroke Limiter
13	265403W	1	Hub, Brake				
14	265402W	1	Cage				
15	267522W	8	Pin				

*a Not used on installations with power controls.

Intermediate Shaft



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
250	2303848W	6	Screw, Flange	255	134074W	3	Shim, 0.005"
251	92623W	1	Cover - Intermediate Shaft	256	134075W	5	Shim, 0.007"
252	92621W	1	Gear, Drum Pinion	257	134076W	2	Shim, 0.020"
253	92620W	1	Shaft, Intermediate	281	30091W	2	Bearing Cup
254	96418W	1	Gear	282	230309W	2	Bearing Cone

Intentionally Blank

Drum Shaft Group

Page 1 of 2

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
292	274464W	1	Keeper, Ferule	319	2303848W	8	Screw, Flange
296	12447W	1	Capscrew	322	141325W	1	Adapter
306	44484W	1	Seal, Oil	323	53559W	12	Thimble, Tapered
307	141149W	1	Seal, Oil	324	2310891	12	Capscrew
308	242839W	1	Drum Shaft	325	131982W	1	Ring
309	78022W	1	Roller Bearing	326	15881W	1	O-Ring
310	173604W	1	Spacer	327	46629W	1	O-Ring
311	96436W	1	Gear, Drum	328	15160W	9	Lockwasher
312	96437W	1	Roller Bearing	370	*a 242832W	2	Nut, Drum Shaft, Narrow/Std
313	96438W	1	Retainer	375	*b 2303654W	2	Nut, Drum Shaft, Wide
314	221641W	8	Capscrew	480	*c 141357W	1	Drum, Overwind
315	173606W	1	Retainer				
316	134070W	AR	Shim, 0.005"				
317	134071W	AR	Shim, 0.007"				
318	134072W	AR	Shim, 0.020"				


*a Standard

*b Used on AW8LP9N***C72

*c Used on AW8L**N***** (Internal Option "N")

Drum Shaft Group

Page 2 of 2




Drum Shaft Group
Extreme Seals (AW8L***S)**
 Page 1 of 2

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
1.1	274464W	1	Keeper, Ferrule				
1.3	12447W	1	Capscrew	1.20	131982W	1	Ring
1.4	2315083	1	Seal, Duo Cone	1.21	15881W	1	O-Ring
1.5	2315084	1	Seal, Duo Cone	1.22	46629W	1	O-Ring
1.6	2316090	1	Shaft, Drum	1.23	15160W	9	Lockwasher
1.7	78022W	1	Roller Bearing	1.24	2302363W	1	Snap Ring
1.8	96436W	1	Gear, Drum	1.25	203550	1	O-Ring
1.9	96437W	1	Roller Bearing	1.26	2316095	1	Retainer - LH Inner
1.10	96438W	1	Retainer	1.27	2316096	1	Retainer - LH Outer
1.11	221641W	8	Capscrew	1.28	2315081	2	Adapter, Ring
1.12	173606W	1	Retainer	1.29	221569W	8	Capscrew
1.13	134070W	3	Shim, 0.005"	1.30	207563	8	Seal
1.14	134071W	3	Shim, 0.007"	1.31	39765W	1	O-Ring
1.15	134072W	1	Shim, 0.020"	1.32	2315067	1	Retainer - RH Outer
1.16	2303848W	8	Screw, Flange	1.33	2315080	1	Ring, Backing
1.17	2316099	1	Adapter	1.34	2315082	2	Adapter, Ring
1.18	53559W	12	Thimble, Tapered	2.1	2316093	1	Drum
1.19	2310891	12	Capscrew	3.1	242832W	2	Nut, Drum Shaft, Narrow/Std

Drum Shaft Group

Extreme Seals (AW8L*****S)

Page 2 of 2




Intentionally Blank

Section 3


Hydraulics/Controls

Hydraulic Group, P-Controls	36 thru 39
Hydraulic Group, E-Controls	40 thru 44
Control Valve Assembly	45
Valve Manifold Assembly	46
Pump	47 thru 48
Handlever Installation, Power Controls	49 thru 51
Handlever Assembly	52
Handlever	53
Joystick Installation, E Controls	54



Hydraulic Group
 Power Controls (AW8LP*****)
 Page 1 of 4




Hydraulic Group
 Power Controls (AW8LP****)
 Page 2 of 4



PUMP SIDE VIEW



Hydraulic Group
 Power Controls (AW8LP****)
 Page 3 of 4



TRANSMISSION CASE PLUMBING
 TOP AND FRONT VIEW

Hydraulic Group
Power Controls (AW8LP***)**
Page 4 of 4

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
1	219172W	1	Strainer	83	259463W	1	Tube Assembly
2	2300936W	1	Cover	85	*e 2300301W	1	Control Valve Assy (See pg 57)
3	2300935W	1	Gasket	86	16829W	1	Capscrew
4	16805W	4	Capscrew	88	17038W	1	Fitting
5	R13812514	10	Lockwasher	89	14595W	1	Fitting
10	1300780W	2	Screw, Ser Flg	90	16568W	1	Fitting
11	18001W	2	Cork	91	139W	1	Pin
13	16989W	2	Fitting	92	15216W	1	Pin
14	16559W	1	Fitting	93	303946W	1	Gasket
15	255433W	1	Connector	94	2314186	1	Fitting
16	14761W	2	Nut	97	2305986W	2	Set Screw
17	19581W	2	Fitting	98	2304823W	1	Plug
18	14723W	2	Fitting	101	16463W	1	Fitting
19	196022W	1	Gasket	103	209790	1	Fitting
20	16828W	2	Capscrew	104	R330325	3	Coupler, Male
21	276087W	1	Hose Assembly	105	209750	1	Fitting
22	225233W	1	Connector - Special	106	212718	1	Fitting
23	177951W	2	Lockwasher	107	209405	1	Fitting
24	255434W	1	Tube Assembly	110	140288W	1	Hose Assembly
25	17309W	1	Fitting	120	*c 303942W	1	Cable, Push/Pull, 82"
26	201431	1	Hose Clamp	120	*d 303944W	1	Cable, Push/Pull, 96"
27	276097W	1	Hose Assembly	125	2307715W	1	Hose Assembly
29	209639W	2	Clamp	126	225704W	1	Hose Assembly
30	201800W	1	Fitting	127	2304358W	1	Fitting
50	202947	2	Hose Clamp	150	276090W	1	Fitting
52	222505W	1	Fitting	152	2307715W	1	Hose Assembly
53	164703W	1	Fitting	154	276092W	1	Hose Assembly
55	165489W	1	Hose Assembly	160	2305114W	1	Bracket - Mounting
58	259456W	1	Tube Assembly	161	1300780W	2	Screw, Ser Flange
59	277663W	1	Tube Assembly	162	2310015	1	Check Valve
60	276095W	1	Tube Assembly	163	2307740W	1	Fitting
61	R14256	1	Hose Assembly	164	16561W	1	Fitting
62	16923W	1	Fitting	165	2300183W	1	Filter Assembly
63	14500W	1	Fitting		3001363W	1	. Element / O-Ring
64	14668W	1	Fitting		55468W	1	.. O-Ring
65	16987W	1	Fitting	166	222381W	1	Fitting
66	16541W	2	Fitting	167	2304360W	1	Hose Assembly
67	83857W	1	Fitting	168	83857W	1	Fitting
68	17300W	1	Fitting	169	R16271	1	Accumulator
69	225232W	1	Adapter - Union	170	2302109W	1	Clamp
70	2314190	1	Fitting	400	*a*e 2302963W	1	Pump Assembly (See page 59)
71	225701W	1	Manifold, Cooling	400	*b*e 2302989W	1	Pump Assembly (See page 60)
73	198385W	3	Capscrew	401	*a 224796W	1	Gear, Pump, 28T
74	15158W	4	Lockwasher	401	*b 2303541W	1	Gear, Pump, 14T
75	279392W	1	Block	402	138750W	1	Locknut
76	226450W	1	Poppet Valve	403	2303677W	1	Fitting
77	225711W	1	Fitting	404	16543W	1	O-Ring
78	276094W	1	Hose Assembly	405	220153	1	Fitting
79	16948W	1	Fitting	406	17040W	1	Fitting
80	16989W	1	Fitting	407	2307730W	1	Fitting
81	277339W	1	Hose				
82	16828W	2	Capscrew				

*a Used on Winches with Gear Ratios #1 and #3


*b Used on Winches with Gear Ratio #9

*c Used on AW8LP**C72 (CAT D7R Series II with P-Controls)

*d Used on AW8LP**C715 (CAT D7GC with P-Controls)

*e See Separate Coverage








Hydraulic Group
E-Controls (AW8LE***)**
 Page 1 of 5





Hydraulic Group

E-Controls (AW8LE*****)

Page 2 of 5

**FITTINGS ON MANIFOLD ASSY.****CLUTCH COOLING OIL LINES****CLUTCH COOLING OIL LINES****BRAKE COOLING OIL LINE****DETAIL A****TRANSMISSION CASE PLUMBING**


Hydraulic Group
E-Controls (AW8LE*****)
Page 3 of 5



Hydraulic Group

E-Controls (AW8LE*****)

Page 4 of 5



CONNECTION	WIRE COLORS	WINCH FUNCTION
BD	ORG & BLK	BRAKE DUMP
BR	PUR & TAN	BRAKE RELEASE
FS (PLUGGED)	GRN & BLK	FREESPOOL
C2	BRN & YEL	REVERSE
C1	BLU & YEL	FORWARD
AC	PINK & BLK	ACCUMULATOR
CO	GRAY & BLK	COOLING
FPS	RED & WHT	PR. SWITCH

Hydraulic Group


E-Controls (AW8LE*****)

Page 5 of 5

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
1.1	219172W	1	Strainer	1.29	210769	3	Fitting
1.2	2300936W	1	Cover	1.30	303946W	1	Gasket
1.3	2300935W	1	Gasket	1.31	2317615	1	Wiring Harness, Internal
1.4	16805W	4	Capscrew	1.32	2312259	1	Plug, Counter
1.5	R13812514	6	Lockwasher	1.33	16561W	1	Fitting
1.6	2316175	1	Tube Assembly, Brake	1.34	211560	1	Fitting
1.7	* 2315717	1	Assembly, Manifold (See page 58)	1.35	129563W	1	Cable Tie
1.8	214316	1	Fitting	1.36	18001W	2	Cork
1.9	222402W	1	Fitting	1.37	16559W	1	Fitting
1.10	1300780W	2	Screw, Ser Flg	1.38	255433W	1	Connector
1.11	236018	1	Hose Assembly	1.39	14761W	2	Nut
1.12	2316948	1	Hose Assembly	1.40	19581W	2	Fitting
1.13	255785	1	Hose Assembly	1.41	14723W	2	Fitting
1.14	253117	1	Hose Assembly	1.42	276087W	1	Hose Assembly
1.15	2316947	1	Hose Assembly	1.43	225233W	1	Connector - Special
1.16	2305987W	3	Setscrew	1.44	177951W	2	Lockwasher
1.17	2312809	1	Kit, Filter & Acc, E-Controls	1.45	255434W	1	Tube Assembly
1.17.1	2305114W	1	. Bracket - Mounting	1.46	209411	1	Fitting
1.17.2	1300780W	2	. Screw, Ser Flg	1.47	201431	1	Clamp, Hose
1.17.3	2310015	1	. Check Valve	1.48	276097W	1	Hose Assembly
1.17.4	2307740W	1	. Fitting	1.49	209639W	2	Clamp
1.17.5	2317441	1	. Assembly, Filter	1.50	16602W	1	Screw
	2305132W	1	. . Filter Head	1.51	2311807	1	Retainer, Connector
	2304112W	1	. . Element, Filter	1.52	178403W	2	Capscrew
	2317424	1	. . Switch, Pressure	1.53	15158W	2	Lockwasher
1.17.6	16543W	1	. O-Ring	1.54	2304366W	1	Plate - Cover
1.17.7	2316749	1	. Hose Assembly	1.55	2305988W	1	Set Screw
1.17.8	2307758W	1	. Tube Assembly	1.56	2317616	1	Adapter Harness
1.17.9	110174W	1	. Fitting	1.57	2317626	1	Programmed Control Module
1.17.10	2305418W	1	. Accumulator	3.1	2304358W	1	Fitting - Hose
1.17.11	2305504W	1	. Clamp	3.2	225704W	1	Hose Assembly
1.18	16541W	1	Fitting	3.3	2307715W	1	Hose Assembly
1.19	18526W	2	Capscrew	4.1	* 2302989W	1	Pump (See page 60)
1.20	18515W	2	Washer	4.2	2303541W	1	Gear, Pump
1.21	2315822	1	Plate, Splash Guard	4.3	138750W	1	Locknut
1.22	133469W	2	Capscrew	4.4	2303677W	1	Fitting
1.23	137852W	2	Cable Tie	4.5	16543W	1	O-Ring
1.24	209412	1	Fitting	4.6	220153	1	Fitting
1.25	214219	1	Fitting	4.7	17040W	1	Fitting
1.26	196022W	1	Gasket	4.8	2307730W	1	Fitting
1.27	279392W	1	Block	5.1	2317456	1	Bluetooth Transmitter (Optional)
1.28	16828W	2	Capscrew				

Control Valve Assembly


Power Controls



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
2300301W Control Valve Assembly							
1	2303001W	1	. Valve Body	18	262088W	1	. Spool Assembly
2	2300308W	1	. Cartridge - Relief	18.1	118365W	1	. . . O-Ring
3	195992W	3	. Spring, Relief	18.2	170987W	8	. . . Ball, Steel
4	195993W	2	. Plug, O-Ring	18.3	238992W	1	. . . Spacer Selector
5	15860W	2	. O-Ring	18.4	2303923W	1	. . . Spring
6	16484W	2	. O-Ring	18.5	166905W	1	. . . Retainer, Spring
7	196004W	2	. Fitting	18.6	196002W	1	. . . Snap Ring
8	15027W	2	. Jam Nut	18.7	196009W	1	. . . Cap
9	195995W	2	. Capscrew	18.8	258220W	1	. . . Ring
10	15962W	2	. Fitting	18.9	196000W	1	. . . Ring
11	118361W	1	. O-Ring	18.10	258217W	1	. . . Spool
12	39376W	1	. O-Ring	18.11	195997W	1	. . . Retainer - Detent
13	196003W	1	. Spool	19	267018W	1	. . . Valve
14	196006W	1	. Spool	20	241778W	2	. . . Bolt
15	226445W	1	. Fitting	21	R13812514	2	. . . Lockwasher
16	15314W	1	. Fitting	22	279397W	1	. . . Cam
17	14595W	1	. Fitting	23	68370W	1	. . . Spring, Pin
				24	14668W	2	. . . Fitting
				25	15483W	2	. . . Fitting

Valve Manifold Assembly


E-Controls (AW8LE*****)



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2315717		Assembly, Valve Manifold				
1	NSS	1	. Block (Blue Color)	5	2310253	1	. Valve, Cartridge
2	2315807	1	. Valve, Relief		254400	1	. . Kit, Seal
	2310260	1	. . Kit, Seal	6	2311558	3	. Coil, 24 VDC Valve
3	2310252	2	. Valve, Cartridge		2315811	3	. Coil, 24 VDC Prop. Valve
	2310258	1	. . Kit, Seal				
4	2315808	3	. Valve, Proportional				
	254396	1	. . Kit, Seal				


Pump - Hydraulic

Gear Ratios #1 thru #7



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
2302963W Pump, Hydraulic							
1	NSS	1	. Plate, Front	10	*a NSS	1	. Washer
2	NSS	1	. Plate, Back	11	NSS	4	. Capscrew
3	NSS	1	. Body	12	*a NSS	1	. Gasket
4	NSS	1	. Gear, Drive	13	*a NSS	1	. Seal
5	316823W	1	. Key	14	NSS	4	. Washer
6	NSS	1	. Gear, Idler	15	NSS	1	. Ring, Retaining
7	*a NSS	1	. Plate, Wear	16	NSS	1	. Plug
8	*a NSS	1	. O-Ring	*a Included in Repair Kit 2302937W			
9	*a NSS	1	. Seal				



Pump - Hydraulic
Gear Ratios #8, #9, and #10



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
2302989W Pump, Hydraulic							
1	NSS	1	. Plate, Front	10	*a NSS	1	. Washer
2	NSS	1	. Plate, Back	11	NSS	4	. Capscrew
3	NSS	1	. Body	12	*a NSS	1	. Gasket
4	NSS	1	. Gear, Drive	13	*a NSS	1	. Seal
5	316823W	1	. Key	14	NSS	4	. Washer
6	NSS	1	. Gear, Idler	15	NSS	1	. Ring, Retaining
7	*a NSS	1	. Plate, Wear	16	NSS	1	. Plug
8	*a NSS	1	. O-Ring	*a Included in Repair Kit 2302937W			
9	*a NSS	1	. Seal				

Handlever Installation - Power Controls

AW8LP**C715 (CAT D7GC with P-Controls)




CONTROL LEVER DETAIL

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
1.10	* 2306703W	1	Handlever (See page 65)	1.14	383881W	1	Nut, Tall
1.11	2317308	1	Lever Mounting	1.15	18717W	1	Capscrew
1.12	232987	3	Capscrew	2	303944W	1	Cable, Push/Pull
1.13	277276W	1	Decal - Handlever				



Handlever Installation - Power Controls

AW8LP**C72 (CAT D7R Series II with P-Controls)

Page 1 of 2




DETAIL C



Handlever Installation - Power Controls

AW8LP**C72 (CAT D7R Series II with P-Controls)


Page 2 of 2



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
60	* 2305202W	1	Handlever Assembly (See pg 64)	66	2304879W	1	Spacer
61	18717W	1	Capscrew	67	296162W	2	Capscrew
62	383881W	1	Nut, Tall	68	2305199W	2	Capscrew
63	277276W	1	Decal - Handlever	69	2305203W	1	Gasket
64	2304569W	1	Gasket	99	303942W	1	Cable, Push/Pull
65	2301055W	2 ¹	Trim (Per Ft)				

Handlever Assembly


AW8LP**C72 (CAT D7R Series II with P-Controls)



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2305202W		Handlever Assembly				
1	2305201W	1	. Bracket - Handlever, W/O FS	3	18127W	3	. Capscrew
2	* 2303982W	1	. Handlever (See page 65)	4	15113W	3	. Locknut

Handlever

Tractor Codes C715, C72



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2303982W	1	Handlever, C72				
	2306703W	1	Handlever, C715				
1 *a -----		2	. Screw	13 *b -----		1	. Adapter, Cable
2 *a -----		2	. Nut	14 *b -----		1	. O-Ring
3 2304339W	1	1	. Knob	15 *b -----		1	. Clevis
4 2304340W	1	1	. Boot	16 NSS		1	. Cover
5 2304341W	1	1	. Nut, Jam	17 NSS		1	. Lever
6 2304342W	2	2	. Bearing, Plastic	18 2304604W		1	. Cover
7 2304343W	1	1	. Screw, Shoulder	19 *c 18717W		1	Capscrew
8 *b -----		1	. Nut	20 383881W		1	Nut, Tall
9 *b -----		1	. Washer				
10 *b -----		1	. Nut				
11 *b -----		2	. Pin, Cotter				
12 *b -----		1	. Pin				




*a Included in 2304338W Cover Attaching Hardware Kit

*b Included in 2305023W Cable Attaching Hardware Kit

*c Use 318702W Thread Lock

Joystick Installation

AW8LE**C72 (CAT D7R Series II with E-Controls)




Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
101	292680W	4	Washer	163 *b	Y35E-#10	4	Washer
102	287816W	4	Capscrew	164 *b	224191	4	Nut, Esna
103	2315078	1	Mounting Plate	165 *b	2304112W	1	Element, Filter
104	2305412W	1	Plate, Joystick Cover	181	2317565	1	Assembly, Joystick
141	2317359	1	Wiring Harness, External	2317612		1	. Decal, Faceplate, Top
142	2307919W	1	Guard, Cable	2317613		1	. Decal, Faceplate, Bottom
143 *a	398817W	2	Screw, Flange	182	2317564	1	Decal, Console
161	137852W	10	Cable Tie	*a Apply Threadlock 318702W			
162	Y25G-(1024)16	4	Capscrew	*b Not Illustrated			


Section 4

Optional Equipment

Fairlead	56 thru 57
Wire Rope Assemblies.....	58

Fairlead, 3-Roller

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
2301944W		3-Roller Fairlead					
1	2301934W	1	. Frame	10	2301942W	1	. Shaft
2	2301726W	2	. Roller	11	16001W	6	. Fitting, Lube
3	2570W	4	. . Bushing	12	15272W	2	Pin
4	2314097	8	. . Washer	13	142809W	2	Bracket
5	2301943W	2	. Shaft	14	93985W	AR	Shim .134
6	2301706W	3	. Keeper	15	15166W	4	Washer
7	398817W	3	. Capscrew	16	18671W	4	Capscrew
8	2301727W	1	. Roller				
9	2570W	2	. . Bushing				

Fairlead, 4-Roller

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
4-Roller Fairlead							
1	2301934W	1	. Frame	10	2301942W	2	. Shaft
2	2301726W	2	. Roller	11	16001W	8	. Fitting, Lube
3	2570W	2	.. Bushing	12	15272W	2	Pin
4	2314097	10	. Washer	13	142809W	2	Bracket
5	2301943W	2	. Shaft	14	93985W	AR	Shim .134
6	2301706W	4	. Keeper	15	15166W	4	Washer
7	398817W	4	. Capscrew	16	18671W	4	Capscrew
8	2301727W	2	. Roller				
9	2570W	2	.. Bushing				

Wire Rope Assemblies

Wire Rope Drum End



Junior Ferrule

Wire Rope Loose End Options



Tail Chain & Hook (TC)



Wedge Socket (WS)



Open Spelter Socket (OS)

Part Number	Wire Rope Diameter	Wire Rope Type	Loose End Type	Loose End Rating (lbs)	Length (ft)	Weight (lbs)	Drum Fill	Wire Rope Breaking Strength (lbs)
WR7-234J	7/8"	EIPS	TC	34,200	234	351	2/3	79,600
WR7-354J					354	522	Full	
YS7-234JWS		EEIPS	WS	70,800	234	351	2/3	87,600
YS354JWS					354	522	Full	
WR8-182J	1"	EIPS	TC	47,700	182	358	2/3	103,400
WR8-275J					275	531	Full	
YS8-182JWS		EEIPS	WS	91,040	182	358	2/3	113,800
YS8-275JWS					275	531	Full	
WR9-145J	1-1/8"	EIPS	TC	47,700	145	363	2/3	130,000
WR9-220J					220	538	Full	
YS9-145JWS		EEIPS	WS	114,400	145	363	2/3	143,000
YS9-220JWS					220	538	Full	
YS9-145JOS		EEIPS	OS	143,000	145	363	2/3	
YS9-220JOS					220	538	Full	

Section 5

Recommended Service Kits

Recommended Winch Service Intervals	60
Recommended Service Kits	61
Filter Kit, P-Controls - 2311167.....	62
Filter Kit, E-Controls - 2311168.....	63
Gasket Kit - 277341W.....	64 thru 65
Clutch Shaft Kit, Gear Ratios 1, 3 - 2311156.....	66
Clutch Shaft Kit, Gear Ratio 9 - 2311157.....	67
Brake Assembly Kit - 2311155.....	68
Brake Shaft Bearing Kit, Gear Ratios 1, 3 - 2311158	69
Brake Shaft Bearing Kit, Gear Ratio 9 - 2311159	70
Clutch Shaft Bearing Kit, Gear Ratios 1, 3 - 2311162	71
Clutch Shaft Bearing Kit, Gear Ratio 9 - 2311163	72
Drum & Intermediate Shaft Bearing and Seal Kit - 2311164	73
Miscellaneous Parts.....	74
Wire Rope Assemblies.....	74
Specialized Tools	74
Tool Kits	75
Diagnostic Tools.....	75

Recommended Winch Service Intervals

Allied Systems Company is pleased to announce an additional tool to keep your customer's winch serviced and functioning properly. Following this recommended service schedule will help keep tractor winch downtime to a minimum, optimize winch operation, and extend the life of your investment. See Table 1 on this page for recommended service intervals, and Table 2 on the next page for recommended service kits.

PTO Winch Maintenance					
Recommended Winch Service Intervals					
Hours or **	Months **	Filter ***	Winch Gear Oil	Brake & Clutch	Major Overhaul
First 250	1	Change			
Every 500	3	Change			
Every 1,000	6		Change		
Every 5,000				* Inspect	
Every 10,000					* Evaluate
Lube rollers and check oil level and filter light weekly.					
* Evaluate = Service based on average winch use; - if used more than once a day, perform overhaul. - if used less than once a day, remove covers and check to determine need.					
* Inspect = Disassemble and inspect for wear.					
** Service winch using the tractor's hour meter or the length of time the winch is mounted to the tractor, whichever occurs first.					
*** Follow tractor schedule if using tractor filter.					
IMPORTANT - For best Load Control Use only the following oils:					
Caterpillar	-Multipurpose Tractor Oil (MTO)				
John Deere	-Hy-Gard				
ExxonMobil	-Mobil Fluid 424 (Factory Fill)				
Chevron	-1000 THF				
	Consult service/operating manual for low temperature oils and other details. Use of non-approved oil may void warranty.				
 2311481 Rev C					

Table 1 Recommended Winch Service Intervals

Recommended Service Kits


SERVICE KITS FOR W8L WINCHES		
Service Description	Kit Description	Kit Part No.
Filter Change (First 250, then every 500 Hours)	Filter Kit	P-Controls
		E-Controls
Complete Oil Change (Every 1,000 hours)	-N/A-	Check our Website for Current Operator's and Service Manuals for Appropriate Oils
Clutch and Brake Overhaul (Every 5,000 hours)	Gasket Kit	277341W
	Clutch Shaft Kit*	Gear ratios 1, 3
		Gear ratio 9
	Brake Assembly Kit	2311157
		2311155
Major Overhaul (Every 10,000 hours)	Pump Assembly	Gear ratios 1, 3
		2302963W
	Brake Shaft Bearing Kit	Gear ratio 9
		2302989W
	Clutch Shaft Bearing Kit	2311158
		2311159
	Drum & Intermediate Shaft Bearing and Seal Kit	2311162
		2311163
		2311164

* Services both clutches. Includes all parts necessary on the clutch shaft; dropdown and PTO bearings and seals must be ordered separately.

Table 2 Routine Maintenance Kits

Filter Kit: 2311167


Unit with P-Controls



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2311167		Filter Kit				
1	3001363W	1	. Element, Filter				
2	2300935W	1	. Gasket				
3	2314005	2	. Gasket, Filter Cover				

Filter Kit: 2311168


Unit with E-Controls



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2311168		Filter Kit				
1	2304112W	1	. Filter, Element				
2	2300935W	1	. Gasket				
3	2314005	2	. Gasket, Filter Cover				

Gasket Kit: 277341W

Page 1 of 2




Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	277341W		Kit, Gasket				
1	55289W	1	. O-Ring	9	* 257779W	1	. Gasket
2	203549	1	. O-Ring	10	* 265332W	1	. Gasket
3	142761W	1	. Gasket	11	286044W	1	. Gasket
4	* 151646W	2	. Gasket	12	2300935W	1	. Gasket
5	* 186460W	1	. Gasket	13	2314005	2	. Gasket
6	196022W	1	. Gasket	14	2314805	1	. Gasket
7	* 226359W	1	. Gasket	15	303946W	1	. Gasket
8	2314804	2	. Gasket				

* Not Illustrated. Not applicable for your winch.


Gasket Kit: 277341W

Page 2 of 2



Clutch Shaft Kit: 2311156

Gear Ratios #1 and #3




Note: Only parts with item numbers
are actually included in this
Service Kit.
All other parts are shown for
reference only.

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
2311156 Clutch Shaft Kit, G/R 1 & 3							
1	2310570	2	. Kit, Clutch Service	9	95581W	4	. Ring, Seal
2	328715W	8	.. Disc, Friction	10	21014W	1	. Nut, Lock
3	261542W	8	.. Plate, Separator	11	174561W	1	. Lockwasher
4	267499W	8	.. Spring	12	58938W	2	. Ring, Snap
5	224793W	4	.. Shim .031	13	39674W	2	. O-Ring
6	89777W	1	.. O-Ring	14	35575W	1	. Ring, Snap
7	79972W	1	.. O-Ring	15	108877W	2	. O-Ring
8	39370W	1	.. O-Ring				

Clutch Shaft Kit: 2311157


Gear Ratio #9



Note: Only parts with item numbers
are actually included in this
Service Kit.
All other parts are shown for
reference only.

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2311157		Clutch Shaft Kit, G/R 9				
1	2310570	1	. Kit, Clutch Service	13	39674W	2	. O-Ring
2	328715W	8	.. Disc, Friction	14	35575W	1	. Ring, Snap
3	261542W	8	.. Plate, Separator	15	108877W	2	. O-Ring
4	267499W	8	.. Spring	16	2300544W	1	. Kit, Clutch Service
5	224793W	4	.. Shim .031	17	328715W	6	.. Disc, Friction
6	89777W	1	.. O-Ring	18	261542W	6	.. Plate, Separator
7	79972W	1	.. O-Ring	19	265407W	8	.. Spring
8	39370W	1	.. O-Ring	20	224793W	4	.. Shim .031
9	95581W	4	. Ring, Seal	21	89777W	1	.. O-Ring
10	21014W	1	. Nut, Lock	22	79972W	1	.. O-Ring
11	174561W	1	. Lockwasher	23	39370W	1	.. O-Ring
12	58938W	2	. Ring, Snap				

Brake Assembly Kit: 2311155




Note: Only parts with item numbers
are actually included in this
Service Kit.
All other parts are shown for
reference only.

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2311155		Brake Assembly Kit				
1	328715W	10	. Disc, Friction	4	133927W	1	. Ring, Piston Seal
2	261542W	9	. Plate, Separator	5	12940W	2	. Snap Ring
3	79979W	1	. O-Ring	6	12915W	2	. Snap Ring

Brake Shaft Bearing Kit: 2311158

Gear Ratios #1, #3




Note: Only parts with item numbers
are actually included in this
Service Kit.
All other parts are shown for
reference only.

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2311158		Brake Shaft Bearing Kit				
1	230311W	1	. Cup, Bearing	3	30080W	1	. Cone, Bearing
2	230310W	1	. Cone, Bearing	4	30059W	1	. Cup, Bearing

Brake Shaft Bearing Kit: 2311159


Gear Ratio #9



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2311159		Brake Shaft Bearing Kit				
1	12940W	1	. Snap Ring	6	2303557W	1	. Cup, Bearing
2	230310W	1	. Cone, Bearing	7	2303558W	1	. Cone, Bearing
3	230311W	1	. Cup, Bearing	8	30080W	1	. Cone, Bearing
4	2303572W	1	. Cone, Bearing	9	30059W	1	. Cup, Bearing
5	2303571W	1	. Cup, Bearing				

Clutch Shaft Bearing Kit: 2311162


Gear Ratios #1, #3



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2311162		Clutch Shaft Bearing Kit				
1	230405W	1	. Bearing Cone	7	225255W	2	. Shim, .005"
2	230351W	2	. Bearing Cup	8	225256W	2	. Shim, .007"
3	230407W	2	. Bearing, Roller	9	225259W	2	. Shim, .005"
5	225262W	1	. Bearing Cone	10	225260W	2	. Shim, .007"
6	41216W	1	. Bearing - Ball				

Clutch Shaft Bearing Kit: 2311163


Gear Ratio #9



Note: Only parts with item numbers
are actually included in this
Service Kit.
All other parts are shown for
reference only.

Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
2311163			Clutch Shaft Bearing Kit				
1	230351W	2	. Bearing Cup	7	2303556W	1	. Bearing Cone
2	225262W	1	. Bearing Cone	8	2303650W	1	. Bearing, Needle
3	230407W	1	. Bearing, Roller	9	225255W	2	. Shim, .005"
4	44326W	1	. Bearing - Ball	10	225256W	2	. Shim, .007"
5	2303554W	4	. Bearing Cup	11	225259W	2	. Shim, .005"
6	2303555W	4	. Bearing Cone	12	225260W	2	. Shim, .007"

Drum & Intermediate Shaft Bearing and Seal Kit



Item	Part No.	Qty	Description	Item	Part No.	Qty	Description
	2311164		Drum & Int Shaft Bearing and Seal Kit				
1	30091W	2	. Cup, Bearing	5	44484W	1	. Seal, Oil
2	230309W	2	. Cone, Bearing	6	141149W	1	. Seal, Oil
3	96437W	1	. Bearing, Roller	7	46629W	1	. O-Ring
4	78022W	1	. Bearing, Roller	8	15881W	1	. O-Ring

Miscellaneous Parts

In addition to the kits listed on the previous pages, Allied Systems Company recommends that you stock the following items.

Allied P/N	Description	Quantity	Order Quantity
2302963W	Assembly, Gear Pump - Ratios 1, 3	1	
2302989W	Assembly, Gear Pump - Ratio 9	1	
2315807	Valve, Relief	1	
2310260	. Kit, Seal	1	
2310252	Valve, Cartridge	2	
2310258	. Kit, Seal	1	
2315808	Valve, Proportional	3	
254396	. Kit, Seal	1	
2310253	Valve, Cartridge	1	
254400	. Kit, Seal	1	
2311558	Coil, Valve - 24VDC	3	
2310259	. Kit, Seal	1	
2315811	Coil, Proportional - 24VDC	3	
95959W	Pin, Drawbar	1	
2303221W	Pin, Retaining	1	

Wire Rope Assemblies

In addition to the kits listed on the previous pages, Allied Systems Company recommends that you stock the following items.

Allied P/N	Description	Length	Will Fill Drum To:	Order Quantity
WR7-234J	Wire Rope Assembly, 7/8", EIPS	234 ft	2/3 Capacity (Recommended)	
WR7-354J	Wire Rope Assembly, 7/8", EIPS	354 ft	Full Capacity	
YS7-234JWS	Wire Rope Assembly, 7/8", EEIPS	234 ft	2/3 Capacity (Recommended)	
YS354JWS	Wire Rope Assembly, 7/8", EEIPS	354 ft	Full Capacity	
WR8-182J	Wire Rope Assembly, 1", EIPS	182 ft	2/3 Capacity (Recommended)	
WR8-275J	Wire Rope Assembly, 1", EIPS	275 ft	Full Capacity	
YS8-182JWS	Wire Rope Assembly, 1", EEIPS	182 ft	2/3 Capacity (Recommended)	
YS8-275JWS	Wire Rope Assembly, 1", EEIPS	275 ft	Full Capacity	
WR9-145J	Wire Rope Assembly, 1-1/8", EIPS	145 ft	2/3 Capacity (Recommended)	
WR9-220J	Wire Rope Assembly, 1-1/8", EIPS	220 ft	Full Capacity	
YS9-145JWS	Wire Rope Assembly, 1-1/8", EEIPS	145 ft	2/3 Capacity (Recommended)	
YS9-220JWS	Wire Rope Assembly, 1-1/8", EEIPS	220 ft	Full Capacity	
YS9-145JOS	Wire Rope Assembly, 1-1/8", EEIPS	145 ft	2/3 Capacity (Recommended)	
YS9-220JOS	Wire Rope Assembly, 1-1/8", EEIPS	220 ft	Full Capacity	

Specialized Tools

Order these specialized tools for installation, maintenance and service of your winch(es).

Allied P/N	Description	Order Quantity
X-201962	Lifting Device	
X-203345	Clutch Shaft Locknut Socket	
X-203346	Clutch Shaft Driver	
X-203348	Lifting Eye	

Section 6

Numerical Index

108877W - 224023W	76
224024W - 2311157	77
2311157 - 41216W	78
41216W - YS9-220JWS	79

Part No.	Page No.	Item	Part No.	Page No.	Item	Part No.	Page No.	Item	Part No.	Page No.	Item
108877W	18	220	141149W	30	307	165489W	39	55	196003W	45	13
108877W	20	220	141149W	73	6	16559W	39	14	196004W	45	7
108877W	66	15	141325W	30	322	16559W	44	1.37	196006W	45	14
108877W	67	15	141348W	22	12	16561W	39	164	196009W	45	18.7
110174W	44	1.17.9	141348W	23	12	16561W	44	1.33	196022W	39	19
110931W	14	22	141348W	24	12	16568W	39	90	196022W	44	1.26
110932W	14	23	141357W	30	480	16602W	10	11	196022W	64	6
110933W	14	24	142761W	2	354	16602W	44	1.5	196025W	27	4
118361W	45	11	142761W	3	407	166396W	4	12	196026W	27	23
118365W	45	18.1	142761W	64	3	166396W	7	2.5	196279W	2	47
123270W	14	21	142809W	56	13	166396W	9	2.5	196279W	3	47
12447W	30	296	142809W	57	13	166905W	45	18.5	196376W	18	237
12447W	32	1.3	14500W	39	63	16805W	39	4	196376W	20	237
12915W	25	380	14595W	2	50	16805W	44	1.4	196435W	22	13
12915W	68	6	14595W	3	50	16828W	39	20	196435W	23	13
12916W	16	79	14595W	39	89	16828W	39	82	196435W	24	13
12940W	26	563	14595W	45	17	16828W	44	1.28	198385W	39	73
12940W	27	12	14668W	39	64	16829W	39	86	19901W	22	
12940W	68	5	14668W	45	24	16923W	39	62	199594W	27	24
12940W	70	1	14723W	39	18	16948W	39	79	200454W	20	527
12944W	17	77	14723W	44	1.41	169671W	16	61	201431	39	26
129563W	7	1.6	14761W	39	16	169671W	17	61	201431	44	1.47
129563W	9	1.6	14761W	44	1.39	16984W	14	9	201800W	39	30
129563W	44	1.35	15027W	45	8	16987W	39	65	202947	39	50
12963W	14	16	15070W	7	2.8	16989W	39	13	203549	25	167
1300780W	39	10	15070W	9	2.7	16989W	39	80	203549	26	167
1300780W	39	161	15113W	52	4	17038W	39	88	203549	64	2
1300780W	44	1.1	15156W	14	12	17040W	39	406	203550	32	1.25
1300780W	44	1.17.2	15158W	18	231	17040W	44	4.7	207563	32	1.3
1308406W	14		15158W	20	231	170987W	45	18.2	209405	39	107
1310819W	7	2.6	15158W	39	74	17300W	39	68	209411	44	1.46
1310819W	9	2.8	15158W	44	1.53	17309W	39	25	209412	44	1.24
1314435W	20	546	15160W	30	328	173604W	30	310	209639W	39	29
131982W	30	325	15160W	32	1.23	173606W	30	315	209639W	44	1.49
131982W	32	1.2	151646W	64	4	173606W	32	1.12	209750	39	105
1321665W	10	2	15166W	56	15	174559W	18	206	209790	39	103
133469W	44	1.22	15166W	57	15	174561W	18	226	21014W	18	227
133898W	17	75	15216W	39	92	174561W	20	226	21014W	20	227
133918W	25	381	15272W	2	48	174561W	66	11	21014W	66	10
133926W	27	7	15272W	3	48	174561W	67	11	21014W	67	10
133927W	27	8	15272W	56	12	177951W	39	23	210769	44	1.29
133927W	68	4	15272W	57	12	177951W	44	1.44	211560	44	1.34
134070W	30	316	15303W	14	19	178402W	14	25	212718	39	106
134070W	32	1.13	15305W	14	4	178402W	18	230	21420W	2	356
134071W	30	317	15307W	18	229	178402W	20	230	21420W	3	409
134071W	32	1.14	15307W	20	229	178403W	44	1.52	214219	44	1.25
134072W	30	318	15314W	45	16	18001W	39	11	214316	44	1.8
134072W	32	1.15	15319W	2	355	18001W	44	1.36	214495W	20	512
134074W	28	255	15319W	3	408	18127W	52	3	219172W	39	1
134075W	28	256	15483W	45	25	18515W	44	1.2	219172W	44	1.1
134076W	28	257	15860W	45	5	18526W	44	1.19	220153	39	405
134078W	16	58	15881W	30	326	186460W	64	5	220153	44	4.6
134078W	17	58	15881W	32	1.21	18671W	56	16	221569W	32	1.29
134079W	16	59	15881W	73	8	18671W	57	16	221641W	30	314
134079W	17	59	15887W	4	5	18717W	49	1.15	221641W	32	1.11
134081W	25	162	15887W	7	1.4	18717W	51	61	221711W	3	414
134081W	26	162	15887W	9	1.4	18717W	53	19	221711W	20	526
134082W	25	163	15962W	45	10	192956W	2	365	221724W	4	11
134082W	26	163	16001W	56	11	192956W	3	365	221725W	9	1.3
134083W	25	164	16001W	57	11	193912W	27	22	221771W	3	413
134083W	26	164	16373W	24	11	194090W	14	11	221771W	20	525
137852W	10	7	16463W	39	101	19581W	39	17	222262W	2	49
137852W	44	1.23	164703W	39	53	19581W	44	1.4	222262W	3	49
137852W	54	161	16484W	45	6	195992W	45	3	222381W	39	166
138750W	39	402	16541W	39	66	195993W	45	4	222402W	44	1.9
138750W	44	4.3	16541W	44	1.18	195995W	45	9	222505W	39	52
139W	39	91	16543W	39	404	195997W	45	18.11	223428	20	513
140184W	27	5	16543W	44	1.17.6	196000W	45	18.9	224023W	18	228
140288W	39	110	16543W	44	4.5	196002W	45	18.6	224023W	20	228

Part No.	Page No.	Item	Part No.	Page No.	Item	Part No.	Page No.	Item	Part No.	Page No.	Item
41216W	71	6	96021W	18	180	WR8-182J	58				
43307W	14	6	96028W	18	181	WR8-182J	74				
44326W	20	535	96417W	25	168	WR8-275J	58				
44326W	72	4	96417W	26	168	WR8-275J	74				
44484W	30	306	96418W	28	254	WR9-145J	58				
44484W	73	5	96431W	18	201	WR9-145J	74				
45310W	16	71	96433W	25	161	WR9-220J	58				
45310W	17	71	96433W	26	161	WR9-220J	74				
45733W	14	18	96436W	30	311	X-201962	74				
46629W	30	327	96436W	32	1.8	X-203345	74				
46629W	32	1.22	96437W	30	312	X-203346	74				
46629W	73	7	96437W	32	1.9	X-203348	74				
53559W	30	323	96437W	73	3	Y17C-2088	4				9
53559W	32	1.18	96438W	30	313	Y25G-(1024)16	54				162
55289W	18	207	96438W	32	1.1	Y25G-0416	3				411
55289W	20	510	96461W	22	8	Y35E-#10	54				163
55289W	64	1	96461W	23	8	YS354JWS	58				
55468W	39		96461W	24	8	YS354JWS	74				
58938W	18	213	96462W	22	3	YS7-234JWS	58				
58938W	20	548	96462W	23	3	YS7-234JWS	74				
58938W	66	12	96462W	24	4	YS8-182JWS	58				
58938W	67	12	96468W	22	11	YS8-182JWS	74				
58947W	14	8	96468W	23	11	YS8-275JWS	58				
67355W	4	14	96524W	17	76	YS8-275JWS	74				
67355W	7	2.12	98362W	16	70	YS9-145JOS	58				
67355W	9	2.14	98362W	17	70	YS9-145JOS	74				
67355W	16	60	NSS	46	1	YS9-145JWS	58				
67355W	17	60	NSS	47	1	YS9-145JWS	74				
68370W	45	23	NSS	47	2	YS9-220JOS	58				
78022W	30	309	NSS	47	3	YS9-220JOS	74				
78022W	32	1.7	NSS	47	4	YS9-220JWS	58				
78022W	73	4	NSS	47	6	YS9-220JWS	74				
79389W	16	78	NSS	47	7						
79389W	17	74	NSS	47	8						
79972W	22	2	NSS	47	9						
79972W	23	2	NSS	47	10						
79972W	24	3	NSS	47	11						
79972W	66	7	NSS	47	12						
79972W	67	7	NSS	47	13						
79972W	67	22	NSS	47	14						
79979W	27	9	NSS	47	15						
79979W	68	3	NSS	47	16						
83857W	39	67	NSS	48	1						
83857W	39	168	NSS	48	2						
89777W	22	6	NSS	48	3						
89777W	23	6	NSS	48	4						
89777W	24	2	NSS	48	6						
89777W	66	6	NSS	48	7						
89777W	67	6	NSS	48	8						
89777W	67	21	NSS	48	9						
90937W	4	16	NSS	48	10						
90937W	7	2.1	NSS	48	11						
90937W	9	2.11	NSS	48	12						
92620W	28	253	NSS	48	13						
92621W	28	252	NSS	48	14						
92623W	28	251	NSS	48	15						
92867W	27	10	NSS	48	16						
93985W	56	14	NSS	53	16						
93985W	57	14	NSS	53	17						
95581W	18	223	R13812514	39	5						
95581W	20	223	R13812514	44	1.5						
95581W	66	9	R13812514	45	21						
95581W	67	9	R14256	39	61						
95959W	2	3	R16271	39	169						
95959W	3	3	R330325	39	104						
95959W	74		WR7-234J	58							
95969W	25	101	WR7-234J	74							
95969W	26	101	WR7-354J	58							
96020W	16	74	WR7-354J	74							

Intentionally Blank



To find a dealer in your area,
Call: (503) 625-2560,
Fax: (503) 625-7269 , or
Email: marketing@alliedsystems.com, or
Visit our website: <http://www.alliedsystems.com>

Allied Systems
COMPANY

599781W-CAT 6/18/2020 Printed in U.S.A.